

# FA60R

60LEDs LED Par

# FA14R

14LEDs 4in1 LED Par



<b>Model</b>		
FANC60-RFN-7C	6694lm	<span style="color:red">●</span> <span style="color:green">●</span> <span style="color:blue">●</span> <span style="color:cyan">●</span> <span style="color:magenta">●</span> <span style="color:yellow">●</span> <span style="color:black">●</span>
FANC60-RFN-5C	5561lm	<span style="color:red">●</span> <span style="color:green">●</span> <span style="color:blue">●</span> <span style="color:cyan">●</span> <span style="color:magenta">●</span> <span style="color:yellow">●</span>
FANC60-RFN-4C	4388lm	<span style="color:red">●</span> <span style="color:green">●</span> <span style="color:blue">●</span> <span style="color:cyan">●</span>
<b>Model</b>		
FANC14-RFN-4C	4200lm	<span style="color:red">●</span> <span style="color:green">●</span> <span style="color:blue">●</span> <span style="color:cyan">●</span>
FANC14-RFN-LC	7400lm	<span style="color:yellow">●</span>
FANC14-RFN-HC	9500lm	<span style="color:white">○</span>



**IP Rating & Voltage**  
Voltage : 110-240V  
IP65

**Light Source**  
14LEDs 10W LED Light Source  
4in1:RGBW

60LEDs 3W  
4Color:RGBW  
5Color:RGBAL  
7Color:RGBALDGDDB  
\*Deep Red, Deep Blue, Indigo  
or other specific colors option  
Lifetime : up to 30000hrs

**Beam Angle**  
60LEDs Version : 10°/15°/30°/45°/60°  
14LEDs Version : 10°/15°/25°/45°

**CCT**  
2800K-10000K

**Power Consumption**  
160W

**Function**  
Thermal System : Natural Cooling  
Linear Dimming Curve  
LCD Display Controller

**Control**  
DMX512

**Others**  
Ambient Temperature : -10 to 40°C  
Frequency : 1.2K

**Standard**  
GB 7000.217

**Accessories**  
In Box : Power Cable , DMX Cable  
Optional : Clamp, Safety Cable

